



LO-9500-R2 en

19" chassis for LO-9500 media converter

- Redundant power supply
- Easy assembly
- Power supply: 2 x 230VAC



The LO-9500-R2 is a 19" chassis to accommodate the media converters of the types LO-9500-xy. Up to 14 media converters can be mounted in the chassis. The redundant power supply ensures high availability. Mounting the media converters is simple. The LO-9500-R2 is delivered with all necessary mounting accessories.

Technical data

General properties

supply voltage	Two redundant power supplies included in the scope of delivery 2 x 110 - 230VAC 50-60Hz
power consumption	Max. 50W when fully equipped with 14 media converters
MTBF	
operating temperature	-20°C to +50°C
dimensions	230 x 490 x 90mm (LxWBxH) 19", 2U
weight	4 kg

Product variants

LO-9500-S

Incl. accessories:
2 power cables
14 slot holders for media converter LO-9500-xy
Blank plates, 3 x 4 slots & 2 x 1 slot



Version 16.11.2022, Changes without notice

barox Kommunikation AG
Im Grund 15
CH-5405 Baden-Dättwil
T.: +41 56 210 45 20

www.barox.ch
www.barox.de
www.barox.at

barox Kommunikation AG
Weiler Strasse 7
D-79540 Lörrach
T.: +49 7621 5500 281