




VI-22301

Industrial PoE Splitter

- Small dimensions
- Delivers PoE+ and separately DC voltage
- Output voltage 12 or 24VDC selectable
- Extended temperature range -40 to 75°C
- Maximum output power 60W



This industrial PoE splitter allows an IP data interface with PoE+ as well as a separate DC voltage of 12 or 24VDC. For example, in addition to a PoE-powered IP camera, a separate light source or heater can be powered. Due to the small dimensions and the wide range of operating temperature, the device is especially suitable for installation in outdoor locations.



Technical data

General properties

supply voltage	PoE+ / PoE++ (PD), max. 60W
power consumption	Max. 60W
operating temperature	-40° to +75°C
dimensions	74 x 54 x 35mm (LxWxH)
weight	0,15kg

interfaces

copper ports	1 x 10/100/1000TX, RJ45, Data & PoE IN (PD), max. 60W 1 x 10/100/1000TX, RJ45, Data & PoE OUT (PSE), max. 30W 1 x DC screw clamps 12/24VDC, max. 30W
--------------	--

network properties

PoE Management	
standards	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3z 1000Base-X Gigabit Ethernet IEEE 802.3af for POE IEEE 802.3at for POE+

Product variants



Version 09.04.2020, Changes without notice