



LO-9500

Media converters for 10/100BaseTX and 10/100/1000TX

- Optical fibre port: 100BaseFX, SC-Duplex
- Copper port: 10/100BaseTX, RJ45
- Simple operation
- Power supply: 5VDC, incl. power supply



This simple media converter can easily be integrated into a network and extends Ethernet connections with fiber optics.



Technical data

General properties

supply voltage	5VDC, power supply included Connector for power: DC connector 5, 5/2,5mm
power consumption	Max. 2W
operating temperature	0°C to 50°C
dimensions	94 x 71 x 26mm (LxWxH)

interfaces

copper ports	1 x 10/100BaseTX, 45RJ or 1 x 10/100/1000TX, RJ45
optical fibre ports	1 x 100BaseFX, SC-Duplex 1 x 1000BaseFX, SFP LC-connector Wavelengths Dual fiber devices: 1310nm Single fiber devices: 1310/1550nm Device with SFP, depending on SFP

network properties

standards	802.3 10BaseT 802.3u 100BaseT(X) and 100BaseFX 802.3X Flow controll
-----------	---------------------------------------------------------------------------

Product variants



**LO-9500-M, LO-9500-S,
LO-9500-BIA-S**

LO-9500-M: 10/100, 2xMM SC-Duplex, 2km, 1310nm
 LO-9500-S: 10/100, 2xSM SC-Duplex, 20km, 1310nm
 LO-9500-BIA-S: 10/100, 1xSM SC, 10km, TX: 1310nm,
 RX: 1550nm



LO-9500-G-SFP

1x10/100/1000TX, 1x1000SFP



LO-9500-R2

19", 2U-rack for max. 14 media converters
 redundant power included, 2x230VAC



LO-9500-R2

Front and back view



LO-9500-R1

19", 1U-Rack for max. 4 media converters
 Without power supplies, each converter must be
 powered individually

Version 06.11.2018, Changes without notice