



## PC-MC101-GE

Industrial media converter for  
10/100/1000BaseTX and SFP

- Variable optics through SFP
- Copper port 10/100/1000TX, RJ45
- FO port 100/1000 SFP
- Extended temperature range -40 to 75°C
- Compact and robust design
- Power supply 12-56VDC



This industrial media converter was developed especially for applications with high data load, such as video over IP or video streaming. The compact design, the wide temperature range and the high flexibility make this media converter ideal for remote locations. By using SFPs with 100 or 1'000 MBit/s the PC-MC101-GE can be connected to practically all common central switches. With the supplied mounting accessories, the media converter can be easily mounted on a DIN rail or on a wall.



## Technical data

---

### General properties

supply voltage	12-56VDC, screw clamps Without power supply, must be ordered separately
power consumption	2W
operating temperature	-40° to +75°C
dimensions	59 x 36 x 50mm (WxHxL)
weight	0,1kg
Testing standards	EMC: CE, FCC, EN 55032/24 EMI: CISPR 32, FCC Part 15B Class A <b>EMS:</b> IEC 61000-4-2 ESD: Contact: 6KV; Air: 8KV IEC 61000-4-4 EFT: Power: 2KV; Signal: 2KV IEC 61000-4-5 Surge: Power: 2KV; Signal: 2KV <b>Vibration:</b> EN 60068-2-6 Shock: EN 60068-2-27 Free Fall: EN 60068-2-32

### interfaces

copper ports	1x10/100/1000BaseTX, RJ45 Auto negotiation Auto MDI/MDI-X Full/Halfduplex
optical fibre ports	1 x 100/1000 SFP, LC-connector Data rate of the SFP must be set by dipswitch

### network properties

standards	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3z 1000Base-X Gigabit Ethernet IEEE 802.3x Flow Control and Back Pressure
-----------	---



## Product variants

---



**PC-MC-101-GE**

For SFP plug-in unit  
LC plug  
Optical data dependent on SFP  
Incl. mounting accessories, without SFP, without power supply



**Mounting accessories**

Supplied mounting accessories for wall and DIN rail mounting

*Version 12.03.2020, Changes without notice*